

• High- capacity, fast colour printers for busy workgroups.

Fast colour laser printers packed into a compact footprint. These high-capacity printers are ideal for demanding workplaces.



Fast and flexible printing

- Full colour printing at either 33 ppm (LBP710Cx) or 38 ppm (LBP712Cx)
- Ideal for busy working environments that demand a reliable, versatile printer.
- The ability to have up to 4 high-capacity paper feeder cassettes (*only available on LBP712Cx)

High-capacity in a small footprint

- Large 650-page capacity as standard, expandable to 2,300 pages (*only LBP712Cx).
- A compact and capable office companion, this larger capacity still comes in a small package.
- Built for versatility, from A5 to A4 double-sided documents, they are ready to deliver in seconds.

Working on the go

- Support for Apple AirPrint (iOS) and Mopria (Android), you can print easily from any compatible device.
- Benefit from more advanced features with the Canon PRINT Business mobile app.
- Google Cloud print-ready for seamless integration.

Higher capacity toner cartridges

- The toner seal inside the cartridge is now automatically removed when the cartridge is fitted, cutting down on waste and installation time.
- In the same compact size, the new Genuine Canon toner cartridges now have a higher capacity, letting you be even more productive.

Canon's exceptional image quality

- These devices produce superior colour graphics, images and text in laser quality prints to make a greater impact on the reader.
- Canon's renowned image expertise ensures that businesses of any size can produce professional looking documents

Smart networking capabilities

- Support for PCL5e/6 and Adobe PostScript printer languages enable hassle-free integration into managed network
- The devices are equally well-suited to managed print service environments and are compatible with Canon's e-Maintenance remote service management system.
- The LBP710 series can also be integrated into Canon's uniFLOW output management platform, bringing you the efficiency and security of My Print Anywhere plus the added benefits of accounting and cost recovery.



PRINT



ETHERNET

Paper Feeder- D1

- Additional 550 sheet paper cassette.
LBP710Cx : 1 in total can be added to main unit
LBP712Cx : 3 in total can be added to main unit

Plain Pedestal- P1

- Place under the device to increase height when free standing

Barcode Printing Kit- F1

- Installs bar code fonts for bar code printing. This kit, which is delivered boxed, includes a license access certificate for activation.

SD Card- C1

- 8GB SD card memory for various functions such as print job spooling, encrypted secured print, secured print, and electronic sort.

PCL Font Set- C1

- Unicode printing capability on SAP and supports Andale font.

i-SENSYS LBP710Cx LBP712Cx



Main unit

**Main unit +
1 Paper Feeder- D1**

**Main unit +
2 Paper Feeders- D1
(LBP712Cx only)**

**Main unit +
3 Paper Feeders- D1
(LBP712Cx only)**

PRINTER ENGINE

Print speed	Single sided (A4): Up to 33/38 ppm colour and mono (LBP710Cx/LBP712Cx) Double sided (A4): Up to 33/38 ipm colour and mono (LBP710Cx/LBP712Cx)
Printing method	Colour laser beam printing
Print quality	Up to 9600 x 600 dpi
Print resolution	Up to 600 x 600 dpi
Warm-up time	Approx. 31 seconds or less from power on
First Page Out Time	Colour: approx. 6.0 seconds Mono: approx. 5.1 seconds
Recommended Monthly Print Volume	2,000 - 6,000 pages per month (LBP710Cx) 2,000 - 7,500 pages per month (LBP712Cx)
Duty cycle	Max. 80,000 pages per month ¹⁾
Print margins	5 mm-top, bottom, left and right

Advanced printing features

Secure Print
Print from USB memory key (JPEG / TIFF / PDF)
Barcode Print²⁾
Google Cloud Print Ready
iOS: AirPrint, Canon PRINT Business app
Android: Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app

MEDIA HANDLING

Paper input (Standard)	550-sheet cassette 100-sheet multi-purpose tray
Paper input (Option)	550-sheet cassette x 1 (LBP710Cx) 550-sheet cassette x 3 (LBP712Cx)
Paper output	200-sheet face down
Media types	Plain paper, Recycled paper, Heavy Paper, Colour paper, Label, Envelope, Post card, Rough paper
Media sizes	Cassette (Standard): A4, B5, A5, A5 (Landscape), LTR, EXE, STMT, K16 Custom size - width: 101.6 to 215.9 mm, length: 148 to 297 mm Multi-purpose tray: A4, B5, A5, A5 (Landscape), A6, LGL, LTR, EXE, FLS, K16, STMT, Index card (3"x5") Custom size - width: 76.2 to 215.9 mm, length: 127 to 355.6 mm Cassette (Optional): A4, B5, A5, A5 (Landscape), LGL, LTR, EXE, STMT, FLS, K16 Custom size - width: 101.6 to 215.9 mm, length: 148 to 355.6 mm
Media weights	Cassette: 60 to 163 g/m ² Multi-purpose tray: 60 to 216 g/m ²
Double sided printing	Automatic Cassette (Standard and optional): A4, B5, A5, LGL, LTR, EXE, FLS, K16 Custom size - width: 148 to 215.9 mm, length: 210 to 355.6 mm 60 to 163 g/m ²

GENERAL FEATURES

Power requirements	220-240V (±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1470W or less Active: Approx. 570W/590W or less (LBP710Cx/LBP712Cx) Standby: Approx. 34W or less Sleep: Approx. 1.3W or less Power switch off: 0.16W or less Typical Electricity Consumption (TEC): 1.4kWh/week Idle time required to enter sleep mode: 1-180 min (default: 1 min) Idle time required to enter Auto Shutdown: 4 hours (default)

Noise level

Sound power³⁾
Active: 65/66 dB (LBP710Cx/LBP712Cx)
Standby: 50/51 dB (LBP710Cx/LBP712Cx)

Sound pressure³⁾
Active: 51 dB
Standby: 37/36 dB (LBP710Cx/LBP712Cx)

Dimensions (W x D x H)

458 mm x 464 mm x 388 mm

Weight

Approx. 28.8 kg

Operating environment

Temperature: 10 to 30°C (50 to 86°F)
Humidity 20 to 80% RH (no condensation)

Control panel

5 Line LCD, 5 LED (Online, Ready, Message, Job and Energy saver), Buttons, 10-key numeric keypad

CONTROLLER

Processor Speed

528MHz + 264 MHz

Memory

1GB

Printer Languages

UFRII (Ultra Fast Rendering), PCL5c⁴⁾, PCL⁵⁾, Adobe[®] PostScript

Fonts

93 PCL fonts, 136 PS fonts

Interface and connectivity

USB 2.0 High-Speed, 10BASE-T/100 BASE-TX/1000BASE-T

Software and Printer Management

Remote User Interface (RUI),
Department ID Management,
Toner Status Tool,
iW Management Console: Server-based software for centralised management of a fleet of devices
eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.
uniFLOW compatibility with uniFLOW Login Device Client for SFP MEAP

Operating Systems Compatibility

Windows[®] 10 / Windows[®] 8.1 / Windows[®] 8 / Windows[®] 7 / Windows[®] Vista / Server[®] 2012R2 / Server[®] 2012 / Server[®] 2008R2 / Server[®] 2008 / Server[®] 2003R2 / Server[®] 2003
Mac OS X version 10.6,8 & up
Linux[®]/C/Unix

CONSUMABLES

All-in-One cartridges

Standard:
Cartridge 040 Black (6,300 pages⁶⁾)
Cartridge 040 Cyan (5,400 pages⁶⁾)
Cartridge 040 Magenta (5,400 pages⁶⁾)
Cartridge 040 Yellow (5,400 pages⁶⁾)
High yield:
Cartridge 040H Black (12,500 pages⁶⁾)
Cartridge 040H Cyan (10,000 pages⁶⁾)
Cartridge 040H Magenta (10,000 pages⁶⁾)
Cartridge 040H Yellow (10,000 pages⁶⁾)
Waste Toner Box: WT-B1 (approx. 54,000 A4 pages)

ACCESSORIES/OPTIONS

Paper Feeder PF-D1 (550-sheet cassette)
SD CARD-C1 (8GB SD card memory)
Barcode Printing Kit-F1 (Enables barcode printing capability)
PCL Font Set-C1 (Enables Unicode printing capability on SAP and supports Andale font)
MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW)
MiCard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW)
Plain Pedestal-P1

Footnotes

¹⁾ Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product

²⁾ Accessory - Barcode Printing Kit-F1 - is required

³⁾ Declared noise emission in accordance with ISO 9296

⁴⁾ Commands supported only. Third party driver or direct printing from application required

⁵⁾ Web distribution only. Driver will be available in October, 2016

⁶⁾ Based on ISO/IEC 19798

⁷⁾ Printer ships with Cartridge 040