

UNCOMPROMISING QUALITY AND PRODUCTIVITY FOR A BROAD RANGE OF CUT-SHEET PRINT APPLICATIONS

Evolve print production with game-changing print speeds, versatile media handling and superb quality



- Supercharge your business's productivity with rapid print speeds of up to 90ppm* in a compact and reliable engine
- Scanning is also more efficient - Up to 300 double-sided sheets can now be scanned in one pass by the DADF (duplex automatic document feeder) with maximum speeds of 230 ipm (mono) and 150 ipm (colour)
- Diversify your workload with flexible media handling. The imagePRESS C910 series now supports paper weights of up to 350gsm and can print banner sheets up to 1,300mm long (simplex)
- Broaden your business applications and produce A4 landscape-fold brochures, book covers, 3-fold and 4-fold leaflets, as well as banners, postcards, personalised direct mail and business cards
- Put quality at the forefront of production. A 190-dot default screen reduces graininess for a crisper output with clearer characters and less moiré
- Refine your production line with an end-to-end solution. Team up an imagePRESS C910 series production press with finishing tools including an in-line ring binder, multi-purpose stacker and third-party finishers thanks to the new Finisher Bridge and DFD Adapter
- Keep production smooth with reliable paper handling. The new robust stack bypass can now hold up to 250 sheets while the DADF colour image reader unit now detects multi-sheet feeding by sensing the air layer between the sheets picked up from the original stack
- Take performance up to the next level with 3 different choices of workflow: EFI, PRISMAsync, Canon PCL and PS

*Print speeds of up to 90ppm with the C910 model.

TECHNICAL SPECIFICATIONS

imagePRESS C910 series

GENERAL SPECIFICATIONS	C910	C810	C710	Dimensions (W x D x H)	
Print speed	up to 90 ppm	up to 80 ppm	up to 70 ppm		1,952 mm* x 934 mm x 1,433 mm** (W x D x H) *Includes optional Control panel and Copy Tray-R2 **Includes Upright Control Panel-G1 (If Operating Panel-A5 and Operator Attention Light-D1 are attached, total height is 1,712 mm)
Recommended monthly volume	40,000 to 167,000 pages (A4)	30,000 to 167,000 pages (A4)	15,000 to 125,000 pages (A4)	Minimum Installation space (W x D)	1,952 (W) x 1,524 (D) mm
Maximum monthly peak volume	Up to 500,000 pages (A4)	Up to 400,000 pages (A4)	Up to 350,000 pages (A4)	Weight	Approx 316kg *Includes ADF
Registration tolerance	Front to Back: 1.0 mm or less			Operating environment	Temperature: 20 to 27°C (50 to 86°F) Humidity: 15 to 60 % RH (no condensation)
Printing method	Colour Laser Beam Printing			Power Source	220-240 V (±10%), 50/60 Hz (±2 Hz), 16A x 2 *All Europe 220-240 V (±10%), 50/60 Hz (±2 Hz), 13A x 2 *UK
Print resolution	2,400 dpi x 2,400 dpi, 256 gradations			Power Consumption	Maximum: Approx 1,560W (at power supply) + 2,500W (at fusing unit) Plug In-Off mode: Approx. 1.0Wh Sleep mode: Approx. 1.5Wh Typical Electricity Consumption (TEC) rating: 10.7kWh (imagePRESS C910), 9.9kWh (imagePRESS C810), 8.9kWh (imagePRESS C710)
Paper capacity	Standard: 3 x 550-sheet cassettes (80 gsm) Option: Stack Bypass-C1: 250* sheet Multi-purpose tray (*1 sheet for Long sheet) POD Deck Lite-C1: 1 x 3,500 sheet side paper deck (A4/A3/SRA3) POD Deck Lite XL-A1: 1 x 3,500 sheet side paper deck (A4/A3/SRA3), 1 x 1,000 sheets of length > 487.7 mm Multi-drawer Paper Deck-C1: 1 x 6,000 sheet (3 x 2,000-sheet cassettes - A4/A3/SRA3)			FIERY PRINT CONTROLLER SPECIFICATIONS	
Maximum paper input capacity	7,650 sheets (A4/A3, 80 gsm)			Optional/Standard Name	Optional imagePRESS Server H350 (External Fiery based server) imagePRESS Server G250 (Embedded Fiery based server)
Maximum paper output capacity	11,200 sheets (A4, 80 gsm)			Page Description Languages	PCL5/6 (Driver & utility support : Only for embedded/ PCL interpreter is available on external Fiery server) Adobe PostScript Level 3
Supported media types	Cassettes: Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Bond, Letterhead, Tab paper*, Transparency, Envelopes** Multi-purpose tray : Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Coated paper, Pre-punched paper, Tab paper, Bond, Transparency, Label, Envelopes, Letterhead Optional paper decks: Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Coated paper, Textured, Bond, Transparency, Label, Letterhead, Tab paper, Envelopes** * Requires Tab feeding attachment ** Requires Envelope feeding attachment			Resolution	1,200 dpi x 1,200 dpi, 600 dpi x 600 dpi
Supported media sizes	Paper cassette 1/2/3 Standard size: A3, A4, A4R, A5R, SRA3, 13"x19" (330 x 483 mm) Free size: 100 x 148 mm to 330.2 x 487.7 mm Envelopes: No.10 (COM10), Monarch, DL, ISO-C5 Stack Bypass-C1 (Multi-purpose tray) Standard size: A3, A4, A4R, A5R, SRA3, 13"x19" (330 x 483 mm) Free size: 100 x 148 mm to 330.2 x 487.7 mm Long sheet*: 210 x 487.8 mm to 330.2 x 1,300 mm Envelopes: No.10 (COM10), Monarch, DL, ISO-C5 *Requires Long Sheet Tray-B1 and Stack Bypass Alignment Tray-D1 POD Deck Lite-C1 Standard size: A3, A4, A4R, A5R, SRA3, 13"x19" (330 x 483 mm) Free size: 139.7 x 148 mm to 330.2 x 487.7 mm Envelopes: No.10 (COM10), Monarch, DL, ISO-C5 POD Deck Lite XL-A1 Standard size: A3, A4, A4R, A5R, SRA3, 13"x19" (330 x 483 mm) Free size: 139.7 x 148 mm to 330.2 x 487.7 mm Long sheet: 210 x 487.8 mm to 330.2 x 762 mm Envelopes: No.10 (COM10), Monarch, DL, ISO-C5 Multi-drawer Paper Deck-C1 Standard size: A3, A4, A4R, A5R, SRA3, 13"x19" (330 x 483 mm) Free size: 139.7 x 182 mm to 330.2 x 487.7 mm Envelope: ISO-C5			Hard Disk Drive	External Fiery based server: 8GB (2 x 4GB) Embedded Fiery based server: 1 x 4 GB External Fiery based server: 1TB SATA Embedded Fiery based server: 500GB SATA External Fiery based server: Up to 3.6 GHz (Intel Core i5-6500) Embedded Fiery based server: 3.3 GHz (Intel Pentium G4400)
Supported media weights	Cassettes: 52 to 300 gsm Multi-purpose tray/Optional paper decks : 52 to 350 gsm Duplex: 52 to 350 gsm Approx. 360 seconds			Processor Speed	138 Adobe PS fonts, 113 PCL fonts, 32 barcode Windows* 7/Windows* 8.1/Windows*10/Windows* Server 2008 R2/Windows* Server 2012 R2/Windows* Server 2016/Mac OS X(10.11-10.14) Ethernet 1000 Base-T/100Base-TX/10Base-T, USB, DVI connector (only for H350), Display Port connector (only for H350)
Warm-up time	Approx. 360 seconds			Network protocols	TCP/IP, AppleTalk (only support font downloader), Bonjour, SNMP, IPP, FTP, SMB, IPv6, WSD(minimum support to achieve WHQL certification) Impose and Compose, GA Package Premium Edition (For H350), Productivity Package (For G250), Removable HDD Kit (For H350)
Interface type	USB 2.0 Hi-speed Ethernet: 1000 BaseT/100Base -TX/10Base-T Standard: 1* x USB Host *Additional one on left side of PRISMAsync operation panel			EFI accessories (Optional)	
Network protocols	TCP/IP* (LPD/Port 9100/WSD/IPP/IPPS/SMB/FTP), IPX/SPX (NDS, Bindery), AppleTalk *IPv4/IPv6 support			PRISMAsync CONTROLLER SPECIFICATIONS	
Processor speed	1.66 GHz (SOC ARM 1136JF-S 400 MHz, ARM 946 200 Mhz)			Optional/Standard Name	Optional PRISMAsync iPR C910 Series
Memory	1.5GB (SOC 2GB)			Page Description Languages	PostScript L3, APPE 5.1, PDF 2.0, IPDS (transactional), PCL/PJL (transactional)
Hard Disk Drive	Standard 1TB Hard Disk Drive			Resolution	PS/PDF: 600 x 600 dpi or 1,200 x 1,200 dpi, transactional PCL: 600 x 600 dpi transactional IPDS: 600 x 600 dpi 2 x 8GB DDR3 @1333MHz SDRAM non-ECC (Dual Channel Mode)
Control panel (for EFI, Canon PS/PCL)	Upright Control Panel-G1: 26.4 cm (10.4 inch) TFT SVGA LED Backlight Colour Upright Touchscreen			Memory	1 x 500GB 2.5 inch SATA III HDD @ 7200 rpm (system disk) 2 x 500GB 2.5 inch SATA III HDD @ 7200 rpm (2 X Data disk) Intel Core i7 4770S CPU @ 3.1 GHz
Control panel (for PRISMAsync)	Operating Panel-A5: 15 inch touch panel screen			Hard Disk Drive	136 Type1 fonts for roman languages User import of PS fonts via Settings Editor Optional Adobe Asian fonts: Japanese: 5 Morisawa fonts (no Heisei fonts) Chinese: 2 fonts for simplified Chinese, 1 font for traditional Chinese Korean: 1 font for Korean
				Processor Speed	7 (32/64 bit), Server 2012R2, 8.1 (32/64bit) and 10 MacOS 10.9 (64 bit), MacOS 10.10 (64 bit), MacOS 10.11 (64 bit), Server 2016, MacOS 10.12/13 (64 bit),
				Fonts	Ethernet (10/100/1000 Base-T), USB for files via operator panel, DVI for connection of operator panel TCP/IP: IPv4 / IPv6, IEEE 802.1x network protocol, SMB (scanning), WebDAV (scanning), FTP (scanning), SMTP (e-mail), SNMP v1/v3, Host resources MIB, System group MIB II, Printer MIB, Job Monitor MIB, Job Management MIB submission via lpr, hotfolders, socket, IPP, JDF/JMF, USB stick.
				Supported Operating Systems	Advance color management, PRISMAsync Remote Match, PRISMAsync remote Control, PRISMalytics Dashboard, DocBox, PageProgramming
				Interface	
				Network protocols	
				PRISMAsync accessories (optional):	



TECHNICAL SPECIFICATIONS

imagePRESS C910 series

SCAN SPECIFICATIONS

Name	Duplex Colour Image Reader Unit-M1
Description	Optional colour flatbed scan unit and 300-sheet duplex automatic document feeder (One-Pass Duplex Scan)
Type	Colour flatbed plus one-pass duplex automatic document feeder
Supported media sizes	A3, A4, A4R, A5, A5R, Free sizes (W x L): Min. 139.7 mm x 128 mm, Max. 432 mm x 304.8 mm
Supported media weights (BW/CL)	Single-sided scanning (BW/CL): 38 to 220 gsm / 64 to 220 gsm; Double-sided scanning (BW/CL): 50 to 220 gsm / 64 to 220 gsm
Scan resolution	Copy: 600 dpi x 600 dpi Send: 600 dpi x 600 dpi / 300 dpi x 300 dpi
Duplex scanning	2-sided to 2-sided (Automatic)
Scan speed	Single-sided (A4, 300 dpi): (BW/CL) 120/120 ipm Double-sided (A4, 300 dpi): (BW/CL) 230/150 ipm Single-sided (A4, 600 dpi): (BW/CL) 120/70 ipm Double-sided (A4, 600 dpi): (BW/CL) 150/85 ipm

SEND SPECIFICATIONS

Optional/Standard	Standard on all models (Requires Duplex Colour Image Reader Unit M1)
Send resolution	100 dpi, 150 dpi, 200 x 100 dpi, 200 dpi, 300 dpi, 200 x 400 dpi, 400 x 200 dpi, 400 dpi, 600 dpi
Destinations	E-Mail/Internet FAX (SMTP), PC (SMB, FTP), WebDAV, Google Docs with IR-ADV Cloud Connect MEAP application
Address Book/Speed dials	LDAP (1000) / Local (Max. 500)
File formats	TIFF, JPEG, PDF, XPS, High compression PDF/XPS, PDF/A-1b, Searchable PDF/XPS, Office Open XML (PowerPoint, Word)
Universal Send Feature Sets	<u>Universal Send Advanced Feature Set-H1 (option):</u> Create outline PDF (Trace and Smooth), Adobe Reader Extensions PDF (Searchable PDF/XPS is a standard feature.) <u>Universal Send Security Feature Set-D1 (option):</u> Send encrypted PDF, and add digital device signature to PDF/XPS files. <u>Universal Send Digital User Signature Kit-C1 (option):</u> Add digital user signature to PDF/XPS files.

COPY SPECIFICATIONS

First Copy Output Time (FCOT)(BW/CL)	Color: Approx. 7.7 sec BW: Approx. 6.9 sec
Copy resolution	Reading: 600 dpi x 600 dpi Printing: 2,400 dpi x 2,400 dpi
Multiple copy	Up to 9,999 copies
Reduction/Enlargement	Zoom: 25-400% in 1% increments Fixed Zoom Ratio: 25%, 50%, 70%, 100%, 141%, 200%, 400%

INPUT ACCESSORY SPECIFICATIONS

POD Deck Lite-C1	Standard size: A3, A4, A4R, A5R, SRA3, 13"x19" (330 x 483 mm) Free size: 139.7 x 148 mm to 330.2 x 487.7 mm Envelopes: No.10 (COM10), Monarch, DL, ISO-C5 Paper Weight: 52 to 350 gsm Paper Capacity: 3,500 sheets (80 gsm) / 4,000 sheets (64gsm) Dimensions (W x D x H): 717 mm x 686 mm x 574 mm Weight: Approx. 76 kg
POD Deck Lite XL-A1	Standard size: A3, A4, A4R, A5R, SRA3, 13"x19" (330 x 483 mm) Free size: 139.7 x 148 mm to 330.2 x 487.7 mm Long sheet: 210 x 487.8 mm to 330.2 x 762 mm Envelopes: No.10 (COM10), Monarch, DL, ISO-C5 Paper Weight: (Up to 487.7 mm length) 52 to 350 gsm (Over 487.7 mm up to 762 mm length) 64 to 300 gsm Paper Capacity: (Up to 487.7 mm length) 3,500 sheets (80 gsm) / 4,000 sheets (64 gsm), (Over 487.7 mm up to 762 mm length) 1,000 sheets (80 gsm) Dimensions (W x D x H): 1,105 mm x 686 mm x 574 mm Weight: Approx. 113 kg
Multi-drawer Paper Deck-C1	Standard size: A3, A4, A4R, A5R, SRA3, 13"x19" (330 x 483 mm) Free size: 139.7 x 182 mm to 330.2 x 487.7 mm Envelope: ISO-C5 Paper Weight: 52 to 350 gsm Paper Capacity: 3 x 2,000 sheets, total 6,000 sheets (80 gsm) / 3 x 2,200 sheets, total 6,600 sheets (64 gsm) Dimensions (W x D x H): 950 mm x 797 mm x 1,040 mm Weight: Approx. 155 kg
Stack Bypass-C1	Standard size: A3, A4, A4R, A5R, SRA3, 13"x19" (330 x 483 mm) Free size: 100 x 148 mm to 330.2 x 487.7 mm Long sheet*: 210 x 487.8 mm to 330.2 x 1,300 mm Envelopes: No.10 (COM10), Monarch, DL, ISO-C5 *Requires Long Sheet Tray-B1 and Stack Bypass Alignment Tray-D1 Paper Weight: 52 to 350 gsm Paper Capacity: 250 sheets (80 or 64 gsm), 1 sheet (Long sheet) Dimensions* (W x D x H): 749 mm x 528 mm x 402 mm *With the Stack Bypass Alignment Tray-D1 and the Long Sheet Tray-B1 Weight*: Approx. 9.5 kg *With the Stack Bypass Alignment Tray-D1 and the Long Sheet Tray-B1

OUTPUT

ACCESSORY SPECIFICATIONS

Staple Finisher-W1 PRO	Upper Tray (A) Capacity: A4/A4R/A5R/A3/SRA3/13"x19" 1,000 sheets (52-300 gsm) / 200 sheets (301-350 gsm) Long sheet (Over 487.7 mm up to 762 mm length) 100 sheets (52-79 gsm) / 50 sheets (80-150 gsm) / 25 sheets (151-300 gsm) / 20 sheets (301-350 gsm) Lower Tray (B) Capacity: A4 4,000 sheets (52-80 gsm) / 3,000 sheets (80.1-300 gsm), A4R 2,000 sheets (52-300 gsm), A3 1,500 sheets (52-300 gsm), SRA3 1,000 sheets (52-300 gsm), Any size 200 sheets (301-350 gsm) Paper Weight: 52 to 350 gsm Staple Position: Corner, Double Staple Capacity: A4: 100 sheets, A3/A4R: 50 sheets Dimensions (W x D x H): 800 mm x 792 mm x 1,239 mm (with Long Sheet Tray : 1,136 mm x 792 mm x 1,239 mm) Weight: Approx. 130 kg Power: 220-240V, 50-60Hz, 8A
Booklet Finisher-W1 PRO	Tray Capacity / Paper Weight / Staple Position / Staple Capacity: same as Staple Finisher-W1 PRO Booklet stitch paper size: A3, A4R, SRA3, 13"x19", Free size (210 x 279.4 mm to 330.2 x 487.7 mm) Booklet stitch paper weight: Body sheet 52-220 gsm, Cover sheet 64-300 gsm Booklet stitch staple capacity: 25 sheets (52-80 gsm, include cover) Dimensions (W x D x H): 800 mm x 792 mm x 1,239 mm (with Long Sheet Tray : 1,136 mm x 792 mm x 1,239 mm) Weight: Approx. 180 kg Power: 220-240V, 50-60Hz, 8A
Puncher Unit-BT1/BU1	Requires either Booklet Finisher-W1 PRO or Staple Finisher-W1 PRO Punch Hole type: BT1: 2 holes and 4 holes (FRN) selectable, BU1: 4 holes (SWE) Punch Paper Weight: 52-300 gsm Punch Paper Size: 2 holes: A3, A4, A4R, Free size (182 x 182 mm to 297 x 432.0 mm excluding 203 x 257 mm to 297 x 270 mm) 4 holes: A3, A4, Free size (257 x 182 mm to 297 x 432 mm) Paper Size: All available size on marking engine Paper Weight: 52 to 350 gsm Output Capacity: 250 sheets at simplex/duplex printing ,100 sheets at length over 487.7 mm (Long Sheet Tray is required) Dimensions (W x D x H): 422 mm x 382 mm x 175 mm Weight: Approx. 1.2 kg
Copy Tray-R2	Paper Size: A3, A4, A4R, A5R, SRA3, 13"x19", Free size (140 x 182 mm to 330.2 x 1,300 mm) Paper Weight: 52 to 350 gsm Output Capacity: 250 sheets at simplex/duplex printing ,100 sheets at length over 487.7 mm (Long Sheet Tray is required) Dimensions (W x D x H): 422 mm x 382 mm x 175 mm Weight: Approx. 1.2 kg
High Capacity Stacker-H1	Paper Size: A3, A4, A4R, A5R, SRA3, 13"x19", Free size (140 x 182 mm to 330.2 x 1,300 mm) Paper Weight: 52 to 350 gsm Output Capacity Stack tray: 6,000 sheets (80 gsm) in two stacks of 3,000 sheets each Top Tray: 200 sheets (80 gsm, 140 x 182 mm to 330.2 x 762 mm), 100 sheets (210 x 762.1 mm to 330.2 x 1,300 mm) Dimensions (W x D x H): 899 mm x 745 mm x 1,040 mm Weight: Approx. 120 kg Power: 90-264V, 47-63Hz, 10A
Perfect Binder-E1	Booklet size: 203 x 138 mm to 297 x 216 mm Booklet thickness: Up to 25mm Cutting Range: Top/bottom: 6.5 to 39.5mm at each edge, fore edge: 6.5 to 49.5mm Body pages: Sizes: A4, SRA4, Free size (257 x 182 mm to 320 x 228.6 mm) Paper weight and number of sheets: Thin Paper (52-63 gsm): 30-200 sheets Plain Paper (64-80 gsm): 10-200 sheets Plain Paper (81-90 gsm): 10-150 sheets Thick Paper (91-105 gsm): 10-150 sheets Thick Paper (106-163 gsm): up to 10 sheets as insertion sheet or up to 25mm as thickness of bunch Cover: Number of Sheets: 1 sheet Sizes: A3, SRA3, Free size (257 x 364 mm to 330.2 x 487.7mm) Paper weight: 90 to 300 gsm Tray capacity: Approx.127mm or approx.1,000 sheets of paper as a total Dimensions : 922 mm x 791 mm x 1,300 mm Weight Approx. 308kg Power: 220-240V, 50/60Hz, 3.0A Number of trays: 2 trays Paper size: A3, A4, A4R, SRA3, 13"x19", Free size (182 x 182 mm to 330.2 x 487.7 mm) Paper Weight: 52 to 300 gsm Paper Capacity: 200 sheets x 2 trays (80 gsm) Dimensions (W x D x H): 336 mm (746 mm including Tray) x 793 mm x 1,407 mm Weight: Approx. 61kg Power: 100-240V, 50/60Hz, 1.0A
Document Insertion Unit-N1	



TECHNICAL SPECIFICATIONS

imagePRESS C910 series

Paper Folding Unit-J1

<Z-Fold> Paper Size: A3, A4R, Paper Weight: 52 to 105 gsm, Output Capacity: same as Staple/Booklet Finisher-W1 PRO
 <C-Fold> Paper Size: A4R, Paper Weight: 52 to 105 gsm, Output Capacity: 40 sheets (81.4 gsm)
 <Accordion Z-fold> Paper Size: A4R, Paper Weight: 52 to 105 gsm, Output Capacity: 40 sheets (81.4 gsm)
 <Double parallel> Paper Size: A4R, Paper Weight: 52 to 90 gsm, Output Capacity: 25 sheets (81.4 gsm)
 <Half fold> Paper Size: A4R, Paper Weight: 52 to 105 gsm, Output Capacity: same as Staple/Booklet Finisher-W1 PRO
 Dimensions (W x D x H): 336 mm x 793 mm x 1,190 mm
 Weight: Approx. 71 kg

Booklet Trimmer-F1

Requires Booklet Finisher-W1 PRO
 Trim Width: 2-28mm
 Trim Thickness: Up to 50 sheets (include cover)
 Paper Weight: 52 to 300 gsm
 Chip tray capacity: Approx. 5,000 sheets (Trim width 20mm, A4, 80 gsm)
 Dimensions (W x D x H): 2,095 mm (including joint, conveyor and output tray) x 790 mm x 1,040 mm
 Weight: Approx. 178 kg (including conveyor and output tray)

Two-Knife Booklet Trimmer-A1

Requires Booklet Trimmer-F1
 Trim Width: 2-15 mm
 Trim Thickness: Up to 50 sheets (include cover)
 Paper Weight: 52 to 300 gsm (Trim 60 to 300 gsm)
 Chip tray capacity: Approx. 1,500 sheets (Trim width 15mm, A4, 80 gsm)
 Dimensions (W x D x H): 2,312 mm (including Booklet Trimmer-F1) x 790 mm x 1,040 mm
 Weight: Approx. 145 kg
 Power: 220-240V, 60Hz, 2.3A

Multi Function Professional Puncher-B1

Paper Weight:
 <Punch> 75-300 gsm (Plain paper), 118-300 gsm (Coated paper)
 <Crease> 157-300 gsm (Plain paper / Coated paper)
 <Through> 75-350 gsm (Plain paper), 118-350 gsm (Coated paper)
 Paper Size:
 <Through> 100 x 148 mm to 330.2 x 1,300 mm
 <Punch> SRA3, A3, SRA4, SRA4R, A4, A4R
 <Crease> SRA3, A3, A4R, 13"x19", 13"x19.2"
 Punch Tools:
 Plastic Comb 21-Hole, Twin Loop 23-Hole (Round/Square), Twin Loop 34-Hole (Round/Square), Color Coil 47-Hole, Velo Bind 12-Hole, Loose Leaf 4-Hole Punch, Loose Leaf 2-Hole Punch, Loose Leaf 4-Hole (Swedish), Crease
 Dimensions (W x D x H): 445 mm x 795 mm x 1,040 mm
 Weight: Approx. 102kg
 Power: 230V, 50Hz, 1.9A

Staple Finisher-AC1 (only compatible with C810 and C710)

Lower Tray (A) Capacity:
 A4/A5R 3000 sheets (81 gsm), A4R/A3/SRA3/13"x19" 1500 sheets (81 gsm),
 Long sheet* (Over 487.7 mm up to 762 mm length) 100 sheets (79 gsm)
 Long sheet* (Over 762mm length) 1 sheet
 All size of thin paper (52-59 gsm) 1,500 sheets
 Capacity for coated paper is half of that for plain paper
 *Long Sheet Tray is required
 Upper Tray (B) Capacity:
 A4/A5R 250 sheets (80 gsm), A4R/A3/SRA3/13"x19" 125 sheets (80 gsm)
 Mid Tray (C) Capacity:
 A4/A5R 250 sheets (80 gsm), A4R/A3/SRA3/13"x19" 125 sheets (80 gsm)
 Paper Weight for Tray A:
 Non Sort 52-350 gsm, Bunch Shift / Staple 52-256 gsm excluding duplex printed thin paper (52-59 gsm) and any special media, Eco Staple 52-105 gsm
 Paper Weight for Tray B/C:
 Non Sort / Bunch Shift 52-256 gsm excluding duplex printed thin paper (52-59 gsm), coated paper (85-105.9 gsm) and any special media
 Staple Position: Corner, Double
 Staple Capacity: <Non coated media, 52-90 gsm>
 A4: 65 sheets, A3/A4R: 40 sheets
 <Coated media> 2 sheets
 Dimensions (W x D x H): 527 mm (Max 656 mm*) x 623 mm x 1,099 mm (Max 1,195 mm*)
 *when the auxiliary tray is extended.
 Weight: Approx. 35 kg

Booklet Finisher-AC1 (only compatible with C810 and C710)

Tray Capacity / Paper Weight / Staple Position / Staple Capacity: same as Staple Finisher-AC1 but if there are any sheets on the saddle tray, the capacity of Tray A becomes limited to 1,500 sheets
 Booklet stitch paper size: A3, A4R, Free size (195 x 270 mm to 304.8 x 457.2 mm)
 Booklet stitch paper weight: Body sheet 52-220 gsm, Cover sheet 52-256 gsm
 Booklet stitch staple capacity (including 1 cover sheet):
 Non coated media; 20 sheets (52-81.4 gsm), 10 sheets (82-105 gsm), 5 sheets (106-150 gsm), 4 sheets (151-209 gsm), 3 sheets (210-220 gsm)
 Coated media; 5 sheets (85-150 gsm), 4 sheets (151-209 gsm), 3 sheets (210-220 gsm)
 Dimensions (W x D x H): 527 mm (Max 656 mm*) x 623 mm x 1,099 mm (Max 1,195 mm*)
 *when the auxiliary tray is extended.
 Weight: Approx. 58 kg

Finisher Jogger Kit-A1

Requires either Staple or Booklet Finisher-AC1.
 Paper Weight: Non Sort 52-300 gsm,
 Bunch Shift 52-256 gsm
 Paper Size: Non Sort A3/A4/A4R, Bunch Shift A3/A4/A4R

2/4 Hole Puncher Unit-A1

Requires either Staple or Booklet Finisher-AC1.
 Punch Hole type: 2 holes and 4 holes (FRN) selectable
 Paper Weight: 52-256 gsm
 Paper Size: 2 holes: A3, A4, A4R 4 holes: A3, A4

4 Hole Puncher Unit-A1

Requires either Staple or Booklet Finisher-AC1.
 Punch Hole type: 4 holes (SWE)
 Paper Weight: 52-256 gsm
 Paper Size: A3, A4, A4R

DFD Adapter-A1

Basic information: Enables DFD connectivity directly beside the engine
 Paper Weight: Plain Paper 52-325 gsm, Coated Paper 128-325 gsm
 Paper Size: 182 x 182 mm - 330.2 x 487.7 mm
 Optionals: Finisher Bridge Height Kit 1002-A1 (Standard DFD height is 860 mm)
 Dimensions (W x D x H): 300 mm x 745 mm x 1040 mm
 Weight: Approx. 60 kg
 Power: 90-264V, 47-63Hz, more than 10A

Finisher Bridge-A1

Basic information: Offers connectivity of Staple Finisher-W1 PRO and Booklet Finisher-W1 PRO with 3rd party DFD finishing equipments. Always in combination with DFD Adapter-A1.
 Paper Weight: Plain Paper 52-325 gsm, Coated Paper 128-325 gsm
 Paper Size: 182 x 182 mm - 330.2 x 487.7 mm
 Dimensions (W x D x H): 600 mm x 745 mm x 150 mm
 Weight: Approx. 30 kg
 Power: Power and control from DFD Adapter-A1

3rd Party Finishers

Basic information: The imagePRESS C910 series can be configured also with 3rd party finishers. Please find here a list of listed and approved finishers.
 SDD BLM300C BookletMaker for Color
 Max Ring Binding Finisher MB-1000C
 Plockmatic BLM35 Booklet Maker and Plockmatic BLM50 Upgrade Kit
 Plockmatic MPS (Multi-Purpose Stacker)
 GBC eWire Pro

Product images are for illustration purposes only. Certain functions are optional. Please refer to the product specifications or contact your Canon sales representative for further details.

Canon Inc.
 canon.com

Canon Europe
 canon-europe.com

English edition
 © Canon Europa N.V., 2019

