PIXMA PRO-200

YOUR TRUE COLOURS, PRINTED TO **PERFECTION**

The aspiring photographer's A3+ printer of choice. Versatile, compact and easy to use, PIXMA PRO-200 prints vibrant, high-quality photos to be proud of.







Impressive high-quality photographs

With a superior 8-colour dye-based ink system, you're guaranteed exceptional reproduction, richer colours, and vibrant professional printing, every time.

· Pick paper that suits you

With versatile media handling and customisable printing sizes, you can enhance your photographs on a variety of paper including fine art, borderless and panoramic.

Quick and easy to use

The built-in 3-inch LCD display lets you check ink levels, perform printer maintenance, and access printer instructions at a glance for excellent results with ease.

Perfect printing every time

With 3 paper feed options and auto paper skew correction function, you can bid farewell to misalignment and printing fails, no matter what paper you're using.

One seamless process

Canon's user-friendly PPL software means you can shoot and send photos with ease from popular photography programs for a onestop edit-to-print experience.



8 Individual Inks





Connectivity

PRODUCT RANGE

Compact size



PRO-300



PIXMA PRO-200



imagePROGRAF PRO-300

PIXMA PRO-200 PIXMA IP8750



TECHNICAL SPECIFICATIONS

PIXMA PRO-200

Class Print Head / Ink Type

Number of Nozzles

Ink Tank **Maximum Printing Resolution** Print Speed Photo (11"x14" image on A3+ with Border Color/PT-101 Black/PT-101

Maximum Printable Paper

Top Tray (width)

Manual Feed (width)

Custom (length) Printable Area Borderless Printing **Bordered Printing**

Support Media Top Tray

Manual Feed

Multi-purpose Tray Paper Size Top Tray

Manual Feed

Multi-purpose Tray Paper Size (Borderless)

Paper Handling (Top Tray) (Maximum Number) Plain Paper Photo Paper Pro Platinum (PT-101)

13" (A3+)

Permanent Total 6 144 nazzles (Y/M/C/PC/PM/Gy/Bk/LGY each 768 nozzles x 8) 8 -color = Y/M/C/PC/PM/Gy/LGy/BK 4800 (horizontal)*1 x 2400 (vertical) dpi

approx 1 m 30s approx.2 m 55s

Top Tray: 322.2 mm (12.7 inch), Borderless Printing : 329 mm (A3+)(13 inch) Manual Feed: 322.2mm (12.7 inch), Borderless Printing: 329 mm (13 inch) 990.60mm (bordered)

Top/Bottom/Right/Left margin: each 0 mm Top margin: 3 mm, Bottom margin: 5 mm/ Left/Right margin: each 3.4 mm (LTR/LGL: Left: 6.4 mm, Right: 6.3 mm) Recommended Top/Bottom/Right/Left margin for Fine Art Paper: each 25 mm

Plain Paper/ Photo Paper Pro Platinum (PT-101)/Photo Paper Plus Glossy II (PP-201)/ Photo Paper Pro Luster (LU-101)/ Photo Paper Plus Semi-gloss (SG-201)/ Matte Photo Paper (MP-101)/ Hagaki/ Lightweight Photo Paper (BOX)/Japanese Paper Washi (BOX)/ Canvas (BOX)/ Red Label Superior 80 g/m2 (WOP111)/ Canon Oce Office Colour Paper 80 g/m2(SAT213)/ Heavyweight Fine Art Paper(BOX)/ Inkjet Greeting Card/Cardstock/Photo Paper Plus Glossy II (PP-208), High Resolution Paper (HR-101N), Photo Paper Glossy (GP-501), Envelope, T-Shirt Transfer, Light Fabric Iron Transfers(LF-101), Dark Fabric Iron Transfers (DF 101)

Photo Paper Pro Platinum (PT-101)/Photo Paper Plus Glossy II (PP-201) /Photo Paper Pro Luster (LU-101)/ Photo Paper Plus Semi-gloss (SG-201)/ Matte Photo Paper (MP-101)/Lightweight Photo Paper (BOX)/ Heavyweight Photo Paper (BOX)/ Japanese Paper Washi (BOX) / Canvas (BOX) / Photo Paper Pro Premium Matte (PM-101) / Heavyweight Fine Art Paper (BOX)/ Extra Heavyweight Fine Art Paper (BOX)/Premium Fine Art Rough/Inkjet Greeting Card/Cardstock/Photo Paper Plus Glossy II (PP-208), Photo Paper Glossy (GP-501), Light Fabric Iron Transfers (LF-101), Dark Fabric Iron Transfers (DF 101) Printable Nail Sticker (NL-101) / Printable Disk

A3+/A3/A4/A5/B4/B5/LTR/LGL/Ledger/Hagaki/7"x10"/ I (3.5"x5")/KG(4"x6") /2I (5"x7")/8"x10"/10"x12"/

Square(127 mm) /210 x594 mm Custum size(width 89 mm - 329 mm, length 127 mm - 990.6 mm) Envelopes(DL, COM10) A3+/A3/A4/B4/LTR/LGL/Ledger/12x12

%10"/10"x12"/210x594 mm Custum size (width 203.2 mm - 330.2 mm, length 254 mm - 990.6 mm)

A3+/A3/A4/LTR/Ledger/Hagaki/7x10/12x12/5x7/L (3.5"x5")/KG (4"x6")/2L(5"x7")/8"x10"/10"x12"/Square (127 mm)/210 x594 mm

ITR/A4/A5/B5 = 100 B4/A3/IGI/IDR = 50L/KG(4"x6") = 20 LTR/A3/A4/2L/8"x10" = 1010"x12"/A3+ = 1

Photo Paper Plus Glossy II (PP-201) Photo Paper Glossy (GP-501)

Photo Paper Pro Luster (LU-101) Photo Paper Plus Semi-aloss

(SG-201) Matte Photo Paper (MP-101) High Resolution Paper (HR-101N)

T-Shirt Transfer Haaaki

Lightweight Photo Paper Japanese Paper Washi Canvas

Red Label Superior 80 g/m2(WOP111) Canon Oce Office Colour Paper 80 g/m2(SAT213) Heavyweight Fine Art Paper Light Fabric Iron Transfers (LF-101)

Dark Fabric Iron Transfers (DF 101)

Envelopes(DL, COM10) Inkjet Greeting Card Cardstock

Photo Paper Plus Glossy II (PP-201)

Paper Handling (Manual Feed) (Maximum Number) Photo Paper Pro Platinum (PT-101)

Photo Paper Plus Glossy II (PP-201) Photo Paper Pro Luster (LU-101)

Photo Paper Glossy (GP-501) Photo Paper Plus Semi-gloss (SG-201)

Matte Photo Paper (MP-101) Lightweight Photo Paper Heavyweight Photo Paper Japanese Paper Washi

Canvas Photo Paper Pro Premium Matte (PM-101)

Heavyweight Fine Art Paper Extra Heavyweight Fine Art Paper Premium Fine Art Rough

(FA-RG1) Light Fabric Iron Transfers (LF-101)

Dark Fabric Iron Transfers (DF 101) Inkjet Greeting Card

Cardstock Photo Paper Plus Glossy II (PP-201)

Paper Handlina (Multi-purpose Tray) (Maximum Number) Paper Weight Top Trav

Manual Feed

Ink End Sensor Print Head Alignment L/KG(4"x6")/Hagaki/Square(127 mm) = 20 LTR/A3/A4/2L/5"x7"/8"x10" = 10 A3+ = 1 L/KG(4"x6") = 20 LTR/A3/A4/2L = 10 A3+ = 1ITR/A4 /A3 = 10 A3+ = 1

L/KG(4"x6") = 20 LTR/A4 /A3/5x7/2L/8"x10" = 10L/KG(4'x6") = 20 LTR/A4 /A3 = 10 A3+ = 1 LTR/A4/B5 = 80 B4 = 50 A3 = 20 A3+ = 1

A4 = 120

 $ITR/A4/A3/A3+/IDR/210 \times 594 mm = 1$ $ITR/A4/A3/A3+/IDR/210 \times 594 mm = 1$ $ITR/A4/A3/A3+/IDR/210 \times 594 mm = 1$ A4 = 100

LTR/A4/A3/A3+/LDR/210x594 mm = 1 LTR/A4 = 1

ITR/A4/7"x10" = 1 ITR/A4 /12"x12" = 1 A4/A3=10 4"x6"=20

A3/A4/LTR/8"x10" /10"x12"/A3+ = 1

ITR/A4/A3/A3+=1

LTR/A4/A3/A3+ = 1

ITP/A4/A3/A3+=1ITR/A4/A3/8"x10" /10"x12"/A3+ = 1

LTR/A4/A3/A3+ = 1LTR/A4/A3/A3+/LDR/210 x 594 mm = 1 LTR/A4/A3/A3+/LDR/210 x 594 mm = 1 LTR/A4/A3/A3+/LDR/210 x 594 mm = 1 LTR/A4/A3/A3+/LDR/210 x5 94mm = 1 LTR/A4/A3/A3+ = 1

LTR/A4/A3/A3+/LDR/210 x 594 mm = 1 LTR/A4/A3/A3+/LDR/210 x 594 mm = 1

LTR/A4/A3/A3+ = 1

1TR/A4/12x12 = 1

LTR/A4/12x12 = 1

ITR/A4/7"x10" = 1 LTR/A4 /12"x12" = 1 A4/A3=1

1 (Multi-purpose Tray)

Plain Paper: 64-105 g/m² Canon Genuine paper (maximum): approx. 380 g/m Canon Genuine paper (maximum): approx. 380 g/m, or Paper Thickness 0.1 ~0.6 mm or less Dot count



TECHNICAL SPECIFICATIONS

PIXMA PRO-200

N/W Protocol Wired IAN Network Type

Data Rate Security Wireless LAN Network Type

Frequency Band Channel Range

Security

Direct connection (Wireless LAN)

PRINTING SOLUTIONS Canon PRINT Inkjet/SELPHY (for iOS/Android)

Layout 1-up(bordered/borderles*4)

1-up(bordered only)

ΔirPrint Layout

1-up(bordered/borderles*4)

1-up(bordered only)

Print Quality*5 Mopria Lavout

1-up (bordered/borderles*4)

1-up(bordered only)

Print Quality*5 Canon Print Service (for Android) Windows 10 Mobile PIXMA Cloud Link From smartphone or tablet Camera Direct Spec. Media size

Compatible Digital Camera

Connecting type File Format Layout *8 1-up(borderless*4) 1-up(bordered*9) Photo Index Print with shooting information 20-up print with shooting 35-up contact print Disc Label File number & date print

SNMP/ HTTP/TCP/IP(IPv4/IPv6)

IEEE 802 3 10base-T IEEE 802.3u 100base-TX 10Mbps/100Mbps(Auto switching) IEEE 802.1x(EAP-TLS/EAP-TTLS/PEAP)

IEEE802.11n/IEEE802.11g/IEEE802.11b IFFF802 11a

2.4GHz / 5GHz 2.4GHz: 1-13 (US: 1-11) and conditions

WEP (64/128bit) WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES)

Available

A4,Letter,A3,A3+,11"x17", Ledger,L,KG(4"x6"), 2L(5"x7"), Square (127"x127"), 7"x10",8"x10", Hagaki

B5,A5,Leaal,B4 Available

A4,Letter,A3,A3+,11"x17",Ledger,L,KG(4"x6"),2L(5"x7"), Square (127"x127"),7"x10",8"x10",10"x12", 12"x 12",210x594, Hagaki

B5,A5,Legal,B4,Envelopes(DL, COM10), Disk, Custom

paper size Draft/Standard/High

Available

A4,Letter,A3,A3+,11"x17",Ledger,L,KG(4"x6"),2L(5"x7"), Square (127"x127") ,7"x10",8"x10",10" x 12" (10x 12) ,12x 12,210x594, Hagaki

B5,A5, Legal, B4, Envelopes(DL, COM10), Disk, Custom paper size

Draft/Standard/High Available

Available

Available

LTR/A4/L/2L(5"x7")/KG (4"x6"/8"x10"/10"x12"/A3/A3+ /Square (127"x127")/Hagaki

"PictBridge" compliant digital cameras, camcorders and camera phones

WLAN

JPEG (Exif ver2.2/2.21/2.3 compliant)*7, PNG

Available Available Available Available Available

Available Available Available[®] GENERAL SPECIFICATIONS

Operation Panel Display Language

Interface USB B Port PictBridge Wireless I AN Operating Environment*12

Recommended Environment * Storage Environment

Quiet Mode

Acoustic Noise (PC Print) Plain Paper(A4, Color)*14 Photo Paper Pro Platinum (PT-101) (L,Color,borderless)

Photo Paper Pro Platinum (PT-101) (4x6,Color, borderless)

Power Power Consumption

Standby (scanning lamp is off) USB connection to PC

OFF

Printing USB connection to PC Standby (all ports connected, scanning lamp is off) <EU only - for ErP Lot 26

regulation> Time to enter Standby mode <EU only - for ErP Lot 26 regulation>

Environment Regulation Eco-Label Dimension(WxDxH)

Factory configuration Output/ADF trays extended Weiaht

INK TANK Ink Model

Page yield (4x6" PT-101) *15

Page yield (A3+ PT-101) *16

3.0 inch/7.5cm LCD(Display Panel, Color)

33 Languages Selectable: Japanese/English(mm & inch)/German/French/Italian/Spanish/Dutch/Portugu ese/Norweaian/Swedish/Danish/Finnish/Russian/Cze ch/Hungarian/Polish/Slovene/Turkish/Greek/Simplifie d Chinese/TraditionalChinese/Korean/Indonesian/ Slovakian/Estonian/Latvian/Lithuanian/Ukrainian/Ro manian/Bulgarian/Thai/Croatian/Vietnamese

Hi-Speed USB

Available

Temperature: 5~35 °C Humidity: 10~90 %RH (no dew condensation) . Temperature: 15∼30 °C Humidity: 10∼80 %RH (no dew condensation)

Temperature: $0\sim40~^\circ\mathrm{C}$ Humidity: $5\sim95~^\circ\mathrm{RH}$ (no dew condensation)

Available

Approx. 42.5db Approx. 42.5db

Approx. 42.2db

AC 100 -240 V 50 /60 Hz

W0.1 xoraaA

Approx 0.2W approx 1.6W

approx. 2.5W

approx. 3 min

approx. 14.1ka

RoHS (EU, China)*, WEEE (EU)* *To be fixed Energy Star* *To be fixed (except for EUR)

approx 639 x 379 x 200 mm approx. 639 x 837 x 416 mm

Chromalife 100+ Ink Tanks: CLI-65 BK/C/M/Y/GY/PC/PM/LGY Number of 10x15cm photos Black (BK): 860 photos* Grey (GY): 595 photos* Light Grey (LGY): 965 photos* Cyan (C): 482 photos* Photo Cyan (PC): 275 photos Magenta (M): 610 photos* Photo Magenta (PM): 320 photos Yellow (Y): 295 photos * Estimated Supplemental Yield Number of A3+ photos Black (BK): 69 photos* Grey (GY): 96 photos* Light Grey (LGY): 139 photos* Cyan (C): 51 photos Photo Cyan (PC): 59 photos* Magenta (M): 77 photos* Photo Magenta (PM): 54 photos Yellow (Y): 55 photos

* Estimated Supplemental Yield

Canon

TECHNICAL SPECIFICATIONS

PIXMA PRO-200

Footnotes:

- [1] Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
- [2] Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734.
- Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host
- computer.

 Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- [3] 1-11 in US, CND, LTN, BRA, TW and HK.
- [4] The amount of image extension beyond the paper cannot be adjusted.
- [5] Resolution may be changed between Direct print and printing from PC.
- [6] They are list of papers which the printer is capable of. The paper type printable from
- Mopria depends on the Mopria's capability.

 |71 Image data taken by DCF (Ver.1.0/2.0) -compliant digital cameras, camcorders or camera phones and recorded in JPEG (Exif-compliant) format.
- (a) Function depends on the connected digital cameras, camcorders or camera phones.
- [9] Plain paper is printed bordered automatically, regardless of the camera settings.
- [10] Not supported for 'Printable Printable Printable Nail Stickerss'.
- [11] Non-support for 2/4/9/16-up in sticker printing as well as date/file number printing in disc label printing.
- The performance of the printer may be reduced under certain temperature and humidity conditions.
- For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions.
- [14] Acoustic Noise is measured based on ISO7779 standard with default setting.
- Is Declared yield value in accordance with ISO/IEC 29102. Values obtained by continuous printing. Right-click the image on Windows 10 and select "Print" from the
- menu to print. [16] When printing ISO/JIS-SCID N2 test file at 11" x 14" continuously on A3+ PT-101, with the default settings of testing paper using Windows 10 printer driver and Photoshop

What's in the box?

- PIXMA PRO-200 EUM/EMB
- Power cord UK type
- Power cord Pan-European type
- · CD-Printing Tray
- Setup software & User's manual CD* *only for Windows
- Users Guide (E-manual)
- European Warranty System (EWS) A3 Leaflet
- Russian Warranty sheet

Canon Inc. canon.com Canon Europe canon-europe.com English edition Canon Europa NV 2020

