

AXIS M5055 PTZ Network Camera

Mini PTZ with HDTV 1080p resolution

AXIS M5055 PTZ Network Camera is an ultra-discreet, palm-sized, pan-tilt-zoom camera for remote indoor monitoring. It provides full frame rate video in HDTV 1080p resolution, and supports multiple H.264 and Motion JPEG video streams. AXIS M5055 is a ceiling-mount camera that provides flexible coverage over a 500 m² (4300 sq. ft) area with $\pm 180^\circ$ pan, 90° tilt, and 5x optical zoom. The IP51 rating ensures protection against dust and dripping water, enabling the camera to operate even when a sprinkler system is activated.

- > **HDTV 1080p**
- > **5x optical zoom and autofocus**
- > **IP51-rated**
- > **Power over Ethernet (IEEE 802.3af)**
- > **Built-in analytics**



AXIS M5055 PTZ Network Camera

Camera	
Image sensor	1/4.85" progressive scan RGB CMOS
Lens	Varifocal. 2.2–11.0 mm, F1.4–F2.5 Horizontal field of view: 14°–71° Vertical field of view: 8°–40° Autofocus
Minimum illumination	Color: 1.2 lux at 30 IRE F1.4
Shutter speed	1/16000 s to 1 s
Pan/Tilt/Zoom	Pan: ±179°, 100°/s Tilt: 90°, 100°/s Zoom: 5x optical, 10x digital 25 preset positions, control queue, on-screen directional indicator
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High profiles Motion JPEG
Resolution	1920x1080 to 320x180 (16:9)
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264
Image settings	Resolution, compression, rotation: 0°, 180°, text and image overlay, color, brightness, sharpness, white balance, wide dynamic range, exposure control, exposure time, gain, exposure zones, exposure priority, image freeze on PTZ, privacy masks
Audio	
Audio streaming	One-way
Audio encoding	AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate
Audio input	Built-in microphone
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log, centralized certificate management
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, Z-Wave Plus [®] HC4 and HC8 ^b
System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection One-click cloud connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at onvif.org
Analytics	Included AXIS Video Motion Detection, audio volume detection, scream detection, removed object detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap
Event triggers	Applications Detectors: live stream accessed Hardware: network Input signal: manual trigger, virtual inputs PTZ: moving, preset reached, ready
	Storage: disruption, recording System: system ready Time: recurrence, use schedule
Event actions	Record video: SD card, network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS network share, email PTZ control: preset position Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text Status LED
Data streaming	Event data
Built-in installation aids	Pixel counter
General	
Casing	IP51-rated plastic casing, clear dome
Sustainability	PVC free
Memory	512 MB RAM, 256 MB Flash
Power	Power over Ethernet 802.3af/802.3at Type 1 Class 3 Typical 4.6 W, max 7.8 W
Connectors	RJ45 10BASE-T/100BASE-TX PoE
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 10–90% RH (non-condensing)
Storage conditions	-30 °C to 60 °C (-22 °F to 140 °F)
Approvals	EMC EN 55032 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN-35 Safety IEC/EN/UL 62368-1 Environment IEC/EN 60529 IP51
Dimensions	Ø130 x 63 mm (Ø5.1 x 2.5 in)
Weight	375 g (0.8 lb)
Included accessories	AXIS M50 Mounting Kit, Installation Guide, Windows decoder 1-user license
Optional accessories	AXIS M50 Clear Dome Cover A For more accessories, see axis.com
Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Warranty	5-year warranty, see axis.com/warranty

- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (eyay@cryptsoft.com).
- Device types in home control group 4: notification sensors. Device types in home control group 8: on/off power switches, power strips, irrigation controls. For more information on the supported command classes, see the product's User Manual.

Environmental responsibility:

axis.com/environmental-responsibility