

EOS R3 OUTPACE. OUTPERFORM.

EOS R3 is designed to capture the fastest moving action. Designed to capture objects moving at high speed and built to meet the exacting demands of professional shooters, with ultra-responsiveness, high sensitivity, reliability and durability.



- Explosive speed at 30fps
- See. React. Respond
- Made for the movies
- Built for professionals
- Advanced connectivity

24.1 MEGA
PIXELS
CMOS

Up to
30
Frames
Per Sec

Eye Control

ISO
102400

60p
6K RAW

IN-BODY
IMAGE
STABILIZER

OPTICAL
IMAGE
STABILIZER

PRODUCT RANGE



EOS 1D X Mark III

EOS 1D X Mark III
EOS R3
EOS R5
EOS R6



EOS R3



EOS R5

Canon

Live for the story_

TECHNICAL SPECIFICATIONS

EOS R3

IMAGE SENSOR		SHUTTER	
Type	36 x 24 mm CMOS	Type	Electronically controlled focal-plane shutter and Electronic shutter function in sensor
Effective Pixels	Approx. 24.1 megapixels	Speed	Mechanical: 30-1/8000 sec (1/2 or 1/3 stop increments), Bulb Electronic: 30-1/64000 (1/2 or 1/3 stop increments up to 1/16000 then 1 stop until 1/64000) (Total shutter speed range. Available range varies by shooting mode)
Total Pixels	Approx. 26.7 megapixels	Shutter Release	Soft touch electromagnetic release
Aspect Ratio	3:2		
Low-Pass Filter	Built-in/Fixed		
Sensor Cleaning	EOS integrated cleaning system	WHITE BALANCE	
Colour Filter Type	Primary Colour	Type	Auto white balance with the imaging sensor
Sensor Shift IS	Yes, up to 8-Stops advantage depending on the lens used ¹	Settings	AWB (Ambience priority/White priority), Daylight, Shade, Cloudy, Tungsten light, White Fluorescent light, Flash, Custom, Colour Temperature Setting White balance compensation: 1. Blue/Amber +/-9 2. Magenta/Green +/-9 Yes, 5 setting can be registered
		Custom White Balance	+/-3 levels in single level increments
IMAGE PROCESSOR		WB Bracketing	3, 2, 5 or 7 bracketed images per shutter release Selectable Blue/Amber bias or Magenta/Green bias
Type	DIGIC X		
		VIEWFINDER	
LENS		Type	0.5-inch OLED colour EVF
Lens Mount	RF (EF and EF-S lenses can be attached using EF TO EOS R ADAPTER, EF TO EOS R ADAPTER WITH CONTROL RING, EF TO EOS R Drop in filter ADAPTER EF-M lenses not compatible)	Dot count	5.76 Million dots (1600x1200)
Focal Length	Equivalent to 1.0x the focal length of the lens with RF and EF lenses 1.6x with EF-S	Coverage (Vertical/Horizontal)	Approx. 100%
		Magnification	Approx. 0.76x ⁵
FOCUSING		Eyepoint	Approx. 23mm (from eyepiece lens centre)
Type	Dual Pixel CMOS AF II	Dioptr Correction	-4 to +2 m ⁻¹ (dioptre)
AF System/Points	With Area 100% horizontal and 100% vertical (Auto selection) ² 100% horizontal and 90% vertical (manual selection) ²	Display performance	Power saving: 59.94 fps Smooth 119.98 fps
AF working range	EV -7.5 - 20 (at 23°C & ISO100) ³	Viewfinder Information	AF point information, Eye Control pointer, Exposure level indicator, Shooting mode, ISO speed, Shutter speed, Aperture, Number of remaining multiple exposures, Exposure compensation, HDR shooting, Highlight tone priority, Multiple-exposure shooting, Multi Shot Noise Reduction, Number of self-timer shooting, Digital Lens Optimizer, Maximum burst, AF method, Battery level, AF operation, Exposure simulation, Drive mode, AEB, Metering mode, FEB, Anti-flicker shooting, Still photo cropping, Aspect ratio, Auto Lighting Optimizer, AE lock, Picture Style, Flash-ready, White balance, Flash off, White balance correction, FE lock, Image Quality, High-speed sync, Bluetooth function, Wi-Fi function, Multi-function lock warning, Histogram, Electronic level, Lens information, focus distance scale, vertical exposure scale, Grid
AF Modes	One Shot Servo AF	Depth of field preview	Yes, via customised button
AF Point Selection	Automatic selection: 1053 Available AF areas when automatically selected Manual selection: 1-point AF (AF frame size can be changed) 4779 AF positions available stills (3969 Movies) Manual selection: AF point Expansion 4 points (up, down, left, right) Manual selection: AF point Expansion surrounding Manual selection: Flexible Zone AF 1-3 (all AF points divided into minimum 9 to 999 maximum focusing zones)	LCD MONITOR	
AF Tracking	Humans, Animals (Dogs, Cats and Birds) or Vehicles (Racing cars or Motor bikes),	Type	8.01 cm (3.2") Clear View LCD II, Approx. 4.15 million dots Approx. 100%
AF Lock	Locked when shutter button is pressed halfway or AF ON is pressed in One Shot AF mode. Using customised button set to AF stop in AI servo	Coverage	Approx. 170° vertically and horizontally
AF Assist Beam	Emitted by built in LED or optional dedicated Speedlite (flash)	Viewing Angle horizontally/vertically	
Manual Focus	Selected on lens	Coating	Anti-smudge.
		Brightness Adjustment	Manual: Adjustable to one of seven levels Colour Tone Adjustment: 4 settings
EXPOSURE CONTROL		Touch-screen operations	Capacitive method with menu functions, Quick Control settings, playback operations, and magnified display. AF point selection in still and Movies, touch shutter is possible in still photo shooting.
Metering modes	Real-time with image sensor, 384-zone metering. (1) Evaluative metering (linked to All AF points) (2) Partial metering (Approx. 5.9% of viewfinder at centre) (3) Spot metering: Centre spot metering (Approx. 2.9% viewfinder at centre) AF point-linked spot metering not provided (4) Centre weighted average metering	Display Options	(1) Basic Camera settings (2) Advance Camera settings (3) Camera settings plus histogram and dual level display (4) No info (5) Quick Control Screen (6) Display off
Metering Brightness Range	EV -3 - 20 (at 23°C, ISO100, with evaluative metering)		
AE Lock	Auto: AE lock takes effect when focus is achieved Manual: By AE lock button in P, Av, Fv, Tv and M modes		
Exposure Compensation	+/-3 EV in 1/3 or 1/2 stop increments (can be combined with AEB)		
AEB	+/-3 EV in 1/3 or 1/2 stop increments		
Anti-flicker shooting	Yes. Flicker detected at a frequency of 100 Hz or 120 Hz. Maximum continuous shooting speed may decrease available with both electronic and mechanical shutter High Frequency anti flicker shooting for M and TV modes		
ISO Sensitivity	Auto 100-102400 (in 1/3-stop or whole stop increments) ISO can be expanded to L:50, H1:204800, ⁴		

Live for the story_

TECHNICAL SPECIFICATIONS

EOS R3

FLASH			
Modes	E-TTL II Auto Flash, Metered Manual	File Numbering	(1)Consecutive numbering (2)Auto-reset (3)Manual reset
X-sync	1/200sec mechanical shutter / 1/250 th electronic 1 st curtain, 1/180sec Electronic shutter	File naming	2 User Presets
Flash Exposure Compensation	+/- 3EV in 1/3 increments with EX series Speedlite flashes	EOS MOVIE	
Flash Exposure Bracketing	Yes, with compatible External Flash	Movie Type	MP4 Video: 4K DCI/ UHD (17.9 / 16.9), Full HD (16.9) 4K/ Full HD: AVC/H.265 variable (average) bit rate, Audio: Linear PCM 4K/ Full HD: MPEG4 AVC/H.264 variable (average) bit rate, Audio: Linear PCM 6K RAW: 12-bit CRM Audio: Linear PCM 6K DCI (17.9) 6000 x 3164 (59.94, 50, 29.97, 25, 24, 23.98 fps) RAW 4K DCI (17.9) 4096 x 2160 (59.94, 50, 29.97, 25, 24, 23.98 fps) Intra or inter frame / light inter frame (4K UHD (16.9) 3840 x 2160 (119.9, 100, 59.94, 50, 29.97, 25, 23.98 fps) intra or inter frame Full HD (16.9) 1920 x 1080 (119.9, 100, 59.94, 50, 29.97, 25, 23.98 fps) intra or inter frame Full HD (16.9) 1920 x 1080 HDR (29.97, 25 fps) inter frame.
Flash Exposure Lock	Yes	Movie Size ⁷	6K RAW 12bit, 4K/ Full HD - YCbCr4:2:2 10bit or YCbCr4:2:2 10bit Yes, Canon Log 3 Max duration 6 hours. (excluding High Frame Rate movies). No 4 GB file limit with exFAT formatted card. ⁸
Second Curtain Synchronisation	Yes, via Speedlite	Colour Sampling (Internal recording)	MOV Video: 4K – DCI 4096x2160 / UHD 3840x2160/ Full HD 1920 x1080 at 100 fps or 119.9 fps ⁹ Recorded as 1/4-speed slow motion movie 8.8-megapixel JPEG still image frame grab from 4K DCI movie possible 8.3-megapixel JPEG still image frame grab from 4K UHD movie possible (HEIF only possible when HDR PQ is set)
Multi-Function shoe/ Hot Shoe/PC terminal	Yes/Yes/Yes	Canon Log	
External Flash Compatibility	E-TTL II with EX series Speedlite, wireless multi-flash support	Movie Length	
External Flash Control	via camera menu screen	High Frame Rate Movie	
SHOOTING		Frame Grab ¹⁰	
Modes	Stills: Flexible priority AE, Program AE, Shutter priority AE, Aperture priority AE, Manual, Bulb and Custom (x3) Movie: Program AE, Shutter priority AE, Aperture priority AE, Manual, and Custom (x3)	Bitrate/Mbps	CRM: 6K RAW (59.97p/50p): Approx. 2600 Mbps 6K RAW (29.97p/25.00p): Approx. 2000 Mbps 6K RAW (24.00p/23.98p): Approx. 1600 Mbps 6K C-RAW (59.97p/50p): Approx. 1800 Mbps 6K C-RAW (29.97p/25.00p): Approx. 900 Mbps 6K C-RAW (24.00p/23.98p): Approx. 720 Mbps MOV: MP4 H.264 Canon Log off: 4K DCI/UHD (119.9p / 100p): Approx. 1880 Mbps 4K DCI/UHD (59.94p/50.00p): ALL-I Approx. 940 Mbps 4K DCI/UHD (59.94p/50.00p): IPB Approx. 230 Mbps 4K DCI/UHD (59.94p/50.00p): IPB Light Approx. 120 Mbps 4K DCI/UHD (29.97p/25.00p/24.00p/23.98p): ALL-I Approx. 470 Mbps 4K DCI/UHD (29.97p/25.00p/24.00p/23.98p): IPB Approx. 120 Mbps 4K DCI/UHD (29.97p/25.00p/24.00p/23.98p): IPB Light Approx. 60 Mbps Full HD (119.9p / 100p): Approx. 360 Mbps Full HD (59.94p/50.00p): ALL-I Approx. 180 Mbps Full HD (59.94p/50.00p): IPB Approx. 60 Mbps Full HD (59.94p/50.00p): IPB light Approx. 35 Mbps Full HD (29.97p/25.00p/24.00p/23.98p):ALL-I Approx. 90 Mbps Full HD (29.97p/25.00p/24.00p/23.98p): IPB Approx. 30 Mbps Full HD (29.97p/25.00p/24.00p/23.98p): IPB Light Approx. 12 Mbps MOV: MP4 H.265 Canon Log on 4K DCI/UHD (119.9p / 100p): Approx. 1880 Mbps 4K DCI/UHD (59.94p/50.00p): ALL-I Approx. 1000 Mbps 4K DCI/UHD (59.94p/50.00p): IPB Approx. 340 Mbps 4K DCI/UHD (59.94p/50.00p): IPB Light Approx. 170 Mbps 4K DCI/UHD (29.97p/25.00p/24.00p/23.98p): ALL-I Approx. 470 Mbps 4K DCI/UHD (29.97p/25.00p/24.00p/23.98p): IPB Approx. 170 Mbps 4K DCI/UHD (29.97p/25.00p/24.00p/23.98p): IPB Light Approx. 85 Mbps Full HD (119.9p / 100p): Approx. 470 Mbps Full HD (59.94p/50.00p): ALL-I Approx. 230 Mbps Full HD (59.94p/50.00p): IPB Approx. 90 Mbps Full HD (59.94p/50.00p): IPB light Approx. 50 Mbps Full HD (29.97p/25.00p/24.00p/23.98p):ALL-I Approx. 135 Mbps Full HD (29.97p/25.00p/24.00p/23.98p): IPB Approx. 45 Mbps Full HD (29.97p/25.00p/24.00p/23.98p): IPB Light Approx. 28 Mbps
Picture Styles	Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined (x3)		
Colour Space	sRGB and Adobe RGB		
Image Processing	Highlight Tone Priority (2 settings) Auto Lighting Optimizer (4 settings) Long exposure noise reduction Clarity High ISO speed noise reduction (4 settings) (still and video) Lens optical correction: - Peripheral illumination correction, Chromatic aberration correction Distortion correction (during/after still photo shooting, during video only) - Diffraction correction, Digital Lens Optimizer (during/after still photo shooting) Resize to M, S1, S2 Cropping: JPEG images can be cropped (Aspect ratios 3:2, 4:3, 16:9, 1:1) Cropping of images - Switch between vertical and horizontal cropping orientation - Image straightening - Cropping frame can be moved using touch screen operation RAW image processing Multiple exposure HDR HEIF to Jpeg conversion		
Drive modes	Single, Continuous High+, Continuous High, Continuous Low, Self-timer (2s+remote, 10s+remote)		
Continuous Shooting	Max. Approx. 12 fps. with Mechanical shutter/1st curtain electronic speed maintained for 1000+ JPEG or 1000 RAW images or 30 FPS with electronic shutter speed maintained for 540 JPEG or 150 RAW images ⁶		
Interval timer	Built in		
FILE TYPE - STILLS			
Still Image Type	RAW 14 bit: RAW and C-RAW (Canon original RAW 3rd edition) JPEG 8 bit: 10 compression options HEIF 10 bit: 10 compression options Complies with Exif 2.31 and Design rule for Camera File system 2.0 Complies with Digital Print Order Format [DPOF] Version 1.1		
RAW+JPEG/HEIF simultaneous recording	Yes, any combination of RAW + JPEG or RAW + HEIF possible,		
Image Size	RAW/ C-RAW: 3:2 ratio 6000x4000, 1.6x (crop) 3744x2496 JPEG/ HEIF: 3:2 ratio (L) 6000x4000, (M) 3984x2656, (S1) 2976x1984, (S2) 2400x1600 1.6x (crop) (L) 3744x2496, (S2) 2400x1600 4:3 ratio (L) 5328x4000, (M) 3552x2664, (S1) 2656x1992, (S2) 2112x1600 16:9 ratio (L) 6000x3368, (M) 3984x2240, (S1) 2976x1680, (S2) 2400x1344 1:1 ratio (L) 4000x4000, (M) 2656x2656, (S1) 1984x1984, (S2) 1600x1600		
Folders	New folders can be manually created, named and selected		

Live for the story_

TECHNICAL SPECIFICATIONS

EOS R3

Dual recording	Yes	INTERFACE	
Microphone	Built-in mono microphone (48 KHz, 16-bit x 2 channels)	Computer	SuperSpeed USB 3.2 Gen 2 USB C connector
HDMI Display	Output to external monitor only (output of images and shooting information, images are recorded to the card) Camera screen and External Monitor output (Simultaneous recording to camera and external recorder, camera screen shows images with shooting information)	Wi-Fi	Wireless LAN (IEEE802.11a/b/g/n/AC) (5 GHz / 2.4 GHz) ¹² , with Bluetooth 5.0 support Features supported - EOS Utility, Smartphone, Upload to image.canon, Wireless printing
HDMI Output	4K (DCI) 59.94p / 50.00p/29.97p /25.00p/24.00p / 23.98p, 4K (UHD) 59.94p / 50.00p/ 29.97p / 25.00p / 23.98p, Full HD 59.94p / 59.94i, 50.00p / 50.00i 480p 59.94p 576p 50p Uncompressed YCbCr 4:2:2, 8-bit or 10-bit, sound output via HDMI is also possible	Other	HDMI mini out (Type D, HDMI-CEC compatible), External Microphone In/Line In (Stereo mini jack), Headphone socket (Stereo mini jack), N3-type terminal (remote control terminal)
Focusing	Dual Pixel CMOS AF II with Eye/Face Detection and Tracking AF (people, animals and vehicles), Movie Servo AF Manual Focus	DIRECT PRINT	
ISO	Auto: 100-25600, H: up to 102400 Manual: 100-25600, H: up to 102400,	PictBridge	Not supported
OTHER FEATURES		STORAGE	
Metadata Tag	User copyright information (can be set in camera) Image rating (0-5 stars) IPTC data (registered with EOS Utility) IPTC data (via MFT app) Image transfer with caption (Caption registered with EOS Utility)	Type	1x CFexpress type B 1x SD/SDHC/SDXC and UHS-II
LCD Panel/Illumination	Yes/Yes	SUPPORTED OPERATING SYSTEM	
Water/Dust resistance ¹¹	Yes	PC & Macintosh	Windows 8.1 and Windows 10 (tablet mode not supported) OS X v10.12, 10.13, 10.14, 10.15. OS 11
Voice Memo	Yes	SOFTWARE	
Intelligent Orientation Sensor	Yes	Image Processing	Digital Photo Professional 4.15.1 or later Digital Photo Professional Express mobile app (iOS only)
Playback zoom	1.5x - 10x in 15 steps	Other	EOS Utility 3 (incl. Remote Capture), Picture Style Editor, WFT Utility, EOS Lens Registration Tool, EOS Web Service Registration Tool, Canon Camera connect app (iOS/Android), Mobile File Transfer app (iOS/Android),
Display Formats	(1)Single image (2)Single image with information (2 levels) Basic - Shooting information (shutter speed, aperture, ISO and Image quality) Detailed - Shooting information (shutter speed, aperture, ISO, metering Image, quality and file size), Lens information, Brightness and RGB histogram, White balance, Picture Style, Color space and noise reduction, Lens optical correction, GPS information, IPTC information (3)4 image index (4)9 image index (5)36 image index (6)100 image index (7)Jump Display (1, 10 or 100 images, start of burst sequence Date, Folder, Movies, Stills, Protected images, Rating) (8)Movie edit (9)RAW processing (10)Rating	POWER SOURCE	
Slide Show	Image selection: All images, by Date, by Folder, Movies, Stills, Protected images or Rating Playback time: 1/2/3/5/10 or 20 seconds Repeat: On/Off	Batteries	Rechargeable Li-ion Battery LP-E19 (supplied) With LCD Approx.860 shots (at 23°C) With Viewfinder Approx. 620 shots (at 23°C) ¹³
Histogram	Brightness: Yes RGB: Yes	Battery life	6 levels + percentage
Highlight Alert	Yes	Battery Indicator	Power turns off after 15 seconds, 30 seconds, 1, 3, 5, 10 or 30 mins
Image Erase	Single image, select range, Selected images, Folder, Card	Power saving	
Image Erase Protection	Erase protection of Single image, Folder or Card all found images (only during image search)	Power Supply & Battery Chargers	Battery charger LC-E19E (supplied), AC Adapter AC-E19 and DC Coupler DR-E19, PD-E1 USB power adapter
Self-Timer	2 or 10 sec.	PHYSICAL SPECIFICATIONS	
Menu Categories	(1)Shooting menu (2)AF Menu (3)Playback menu (4)Network (5)Setup menu (6)Custom Functions menu (7)My Menu	Body Materials	Magnesium Alloy body and polycarbonate with glass fibre
Menu Languages	29 Languages English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Vietnamese, Hindi, Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified Chinese, Traditional Chinese, Korean, Malay, Indonesia and Japanese	Operating Environment	0 - 40 °C, 85% or less humidity
Firmware Update	Update possible by the user via menu or Camera connect App (Camera, Lens, External Speedlite, BLE remote control, Lens adapter)	Dimensions (WxHxD)	150x 142.6 x 87.2mm
		Weight (body only)	Approx. 822 g (1015g with card and battery)
		ACCESSORIES	
		Wireless File Transmitter	None
		Lenses	All RF lenses (EF & EF-S via Lens adapters)
		Lens adapters	EF TO EOS R ADAPTER, EF TO EOS R ADAPTER WITH CONTROL RING, EF TO EOS R Drop in filter ADAPTER
		Flash	Canon Speedlite (EL-1 ¹⁴ , EL-100, 90EX, 220EX, 270EX, 270EX II, 320EX, 380EX, 420EX, 430EX, 430EX II, 430EX III 470EX-AI, 550EX, 580EX ¹⁴ , 580EX II ¹⁴ , 600EX ¹⁴ , 600EX-RT ¹⁴ , 600EX-II-RT ¹⁴ , Macro-Ring-Lite MR-14EX, Macro Ring Lite MR-14EX II, Macro Twin Lite MT-24EX, Macro Twin Lite MT-26EX Speedlite Transmitter ST-E2, Speedlite Transmitter ST-E3-RT ¹⁴ , Speedlite Transmitter ST-E3-RT V2 ¹⁴ , Speedlite Transmitter ST-E10)
		Remote Controller/Switch	Remote control with N3 type socket, Speedlite 600EX-II-RT, Speedlite EL-1 and BR-E1 Bluetooth remote
		Other	Eyecup ER-h, Eyecup ER-he, Multi-Function Shoe Adapter AD- E1, Multi-Function Shoe Directional Stereo Microphone DM-E1D (Mic), Multi-Function Shoe Adapter for Smartphone Link AD-P1 for Android (phone holder), Stereo Microphone DM-E1 / DM-E100

Live for the story_

TECHNICAL SPECIFICATIONS

EOS R3

All data is based on Canon standard testing methods except where indicated.
Subject to change without notice.

Footnotes:-

- ¹ 8 stops based on the CIPA standard with RF 24-105mm F4 L IS USM at a focal length of 105mm
- ² The AF area available vary depending on the lens used
- ³ The lowest light AF is available with an f/1.2 lens, centre AF point, One-Shot AF, at 23°C / 73°F, ISO 100 Except RF lenses with a Defocus Smoothing (DS) coating
- ⁴ Recommended Exposure Index
- ⁵ with 50mm lens at infinity, -1m⁻¹ dpt
- ⁶ Under Canon testing standards with CFexpress card and during servo AF, only RF lenses and some EF lenses can be used for continuous shooting at the maximum speed. For details on supported lenses, refer to Canon's official website.
The continuous shooting speed may be reduced by the lens, shutter speed, aperture, flash, flicker reduction processing, subject conditions, and brightness (for example, when shooting in a dark place).
- ⁷ 4K UHD is 94% horizontal coverage of the image area, Full HD is 100%, 4K movie cropping mode is 62% of the horizontal area
- ⁸ If the camera's internal temperature becomes too high the maximum recording time will be reduced
- ⁹ In High frame Rate Movie mode sound is not recorded
- ¹⁰ Frame grab is not available for RAW movies or Canon Log 3 movies.
- ¹¹ Although the camera features dust- and water-resistant construction, this cannot completely prevent dust or water droplets from entering the camera.
- ¹² Wi-Fi use may be restricted in certain countries or regions
- ¹³ Based on the CIPA Standard and using the battery supplied with the camera, except where indicated. In power saving mode
- ¹⁴ Must use Multi-Function Shoe Adapter AD-E1 to retain weather sealing



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2021

Live for the story_

OUTPACE. OUTPERFORM.

EOS R3

EOS R3 is designed to capture the fastest moving action. Designed to capture objects moving at high speed and built to meet the exacting demands of professional shooters, with ultra-responsiveness, high sensitivity, reliability and durability.

Sale Start Date: November 2021



PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
EOS R3 EU1 5 GHz EUME26	4895C004AA	4549292183214	<Please fill in RRP>
EOS R3 EU2 2.4 GHz MEARSACE	4895C005AA	4549292183221	<Please fill in RRP>

OPTIONAL ACCESSORIES:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
Power Supply			
CAMERA BATTERY PACK LP-E19	1169C002AA	4549292060560	<Please fill in RRP>
Battery Charger LC-E19	1170C003AA	4549292060591	<Please fill in RRP>
AC Adapter AC-E19	1171C003AA	4549292068795	<Please fill in RRP>
DC Coupler DR-E19	1172C001AA	4549292066050	<Please fill in RRP>
USB Power Adapter PD-E1	3250C003AA	4549292125412	<Please fill in RRP>
Cables			
Interface Cable IFC-100U	3224C001AA	4549292124200	<Please fill in RRP>
Interface Cable IFC-400U	3225C001AA	4549292124224	<Please fill in RRP>
Miscellaneous			
^[NEW] Stereo Microphone DM-E1D	5138C001AA	4549292185782	<Please fill in RRP>
Stereo Microphone DM-E100	4474C001AA	4549292164992	<Please fill in RRP>
^[NEW] Multifunction Shoe Adapter AD- E1	4943C001AA	4549292184549	<Please fill in RRP>
Remote Switch RS-80N3	2476A001AA	4960999581576	<Please fill in RRP>
Timer Remote Controller TC-80N3	2477A004AA	4960999581569	<Please fill in RRP>
Wireless Remote-Control BR-E1	2140C001AA	4549292087864	<Please fill in RRP>
^[NEW] Eyecup ER-h Small	4896C001AA	4549292181180	<Please fill in RRP>
^[NEW] Eyecup ER-hE Large	4897C001AA	4549292181197	<Please fill in RRP>
^[NEW] Multi-Function Shoe Adapter for Android smartphones	5553C001AA	4549292195378	<Please fill in RRP>
^[NEW] Strap ER-L1	4898C001AA	4549292181203	<Please fill in RRP>
Hand Strap E2	4991B001AA	4960999686202	<Please fill in RRP>

Live for the story_

OUTPACE. OUTPERFORM.

EOS R3

EOS R3 is designed to capture the fastest moving action. Designed to capture objects moving at high speed and built to meet the exacting demands of professional shooters, with ultra-responsiveness, high sensitivity, reliability and durability.



OPTIONAL ACCESSORIES:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
Lenses			
LENS RF 15-35mm F2.8L IS USM EU26	3682C005AA	4549292152272	<Please fill in RRP>
LENS RF 24-70mm F2.8L IS USM EU26	3680C005AA	4549292148381	<Please fill in RRP>
LENS RF 70-200mm F2.8L IS USM EU26	3792C005AA	4549292156263	<Please fill in RRP>
LENS RF 400mm F2.8L IS USM	5053C005AA	4549292184440	<Please fill in RRP>
LENS RF 600mm F4L IS USM	5054C005AA	4549292184457	<Please fill in RRP>
Mount Adapter			
MT ADAPTER EF-EOS R	2971C005AA	4549292115703	<Please fill in RRP>
CONTROL RING MOUNT ADAPTER EF-EOS R	2972C005AA	4549292115710	<Please fill in RRP>
DIF MT ADAPTER EF-EOS R WITH V-ND FILTER	3443C005AA	4549292141610	<Please fill in RRP>
DIF MT ADAPTER EF-EOS R WITH C-PL FILTER	3442C005AA	4549292141603	<Please fill in RRP>
Flash related accessories			
Speedlite 600EX II-RT EU16	1177C006AA	8714574643281	<Please fill in RRP>
Macro Ring Lite MR-14EX II	9389B003AA	4549292007749	<Please fill in RRP>
Macro Twin Lite MT-26EX	2398C003AA	4549292102895	<Please fill in RRP>
Speedlite Transmitter ST-E3-RT (Ver.2)	5743B012AA	4549292192568	<Please fill in RRP>
^{NEW} Speedlite Transmitter ST-E10	4944C001AA	4549292184556	<Please fill in RRP>
Speedlite EL-1	4571C010AA	8714574667881	<Please fill in RRP>

Live for the story_

OUTPACE. OUTPERFORM.

EOS R3

EOS R3 is designed to capture the fastest moving action. Designed to capture objects moving at high speed and built to meet the exacting demands of professional shooters, with ultra-responsiveness, high sensitivity, reliability and durability.



MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Gross Weight (kg)
EOS R3 EU1 5 GHz EUME26 EOS R3 EU2 2.4 GHz MEARSACE	4895C004AA 4895C005AA	EA	Each	1	24.1	20	19.8	2.12
		CT	Carton	4	42	41.6	28.9	9.45
		EP	Euro Pallet	24	120	80	101.4	66.7
			Layers per Pallet	3				
			Cartons per Layer	2				
			Products per layer	8				

What's in the box?

5 GHz version

- EOS R3 Body
- Eyecup ER-h small
- Accessory shoe cover (Dust and water resistant)
- Camera Cover R-F-5
- Strap ER-L1
- Battery Charger LC-E19
- Battery Pack LP-E19
- Battery Pack Cover
- Power Cable (EU)
- Interface Cable IFC-100U (No core)
- Interface Cable IFC-100U protector
- User Manual (EU1)

2.4 GHz version

- EOS R3 Body
- Eyecup ER-h small
- Accessory shoe cover (Dust and water resistant)
- Camera Cover R-F-5
- Strap ER-L1
- Battery Charger LC-E19
- Battery Pack LP-E19
- Battery Pack Cover
- Power Cable (EU)
- Interface Cable IFC-100U (No core)
- Interface Cable IFC-100U protector
- User Manual (EU2)

Live for the story_