

RF 100-300mm F2.8L IS USM

ALL THE BENEFITS OF A ZOOM. ALL THE QUALITIES OF A PRIME

A compact, lightweight professional f/2.8 telephoto zoom that offers exceptional sharpness and speed with unparalleled flexibility.



- A pro zoom with versatile telephoto power
- Blazingly fast, responsive and precise
- Incredible image quality
- Creative control when you need it most
- Built for professionals
- Add even more versatility with RF extenders

PRODUCT RANGE



RF 70-200mm
F2.8L IS USM

RF 70-200mm
F2.8L IS USM

**RF 100-300mm
F2.8L IS USM**

RF 400mm
F2.8L IS USM



**RF 100-300mm
F2.8L IS USM**



RF 400mm
F2.8L IS USM

Canon

Live for the story_

TECHNICAL SPECIFICATIONS

RF 100-300mm F2.8L IS USM

OPTICAL FEATURES / SPECIFICATIONS

Angle of View (Horzntl, Vertl, Diagnl)

20° - 6° 50',
14° - 4° 35',
24° - 8° 15',
23/18

Lens construction (elements/groups) Special optics

1x Fluorite
4x UD
1x GMo aspherical

No. of diaphragm blades

9

Minimum aperture

22

Closest focussing distance (m)

1.8m (constant)

Maximum magnification (x)

0.06 (at 100mm)
0.16 (atr 300mm)

Control ring

Yes

Image stabilizer¹ No. Stops

Yes

Lens OIS only

5.5

IBIS x OIS

6

AF actuator

Dual Nano USM

Coatings

ASC, Super Spectra

Fluorine coating

Front

PHYSICAL SPECIFICATIONS

Dust/moisture resistance²

Yes

Exterior coating

Heat Shield

Filter diameter (mm)

112

Max. diameter x length (mm)

128 x 323.4

Weight (g)

2590

ACCESSORIES

Lens Cap

E-112

Lens hood

ET-124

Lens case/pouch

Lens Soft Case LS100-300

Rear End Cap

Lens Dust Cap RF

Extender Compatibility

Compatible with RF Extender only

SPECIFICATIONS 1.4X EXTENDER

Focal Length

140mm-420mm

Aperture values (f/)

4

Maximum Magnification

0.22

AF Possible

Yes

IS

Yes

SPECIFICATIONS WITH 2X EXTENDER

Focal Length

200mm - 600mm

Aperture values (f/)

5.6

Maximum Magnification

0.31

AF Possible

Yes

IS

Yes

Footnotes/Disclaimers

¹ Tested under CIPA standards

² Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

What's in the box?

- LENS RF 100-300mm F2.8L IS USM
- E-112 LENS CAP
- LENS DUST CAP RF
- ET-124 LENS HOOD
- LENS SOFT CASE LS100-300
- LENS WIDE STRAP B
- User Manual (EUR)

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2023

Live for the story_